

TM9356 DUAL BAND MOBILE

SPECIFICATIONS



Tait DMR: a smart investment, made to evolve.

The TM9356 mobile provides dual frequency band capability for DMR Tier 2 and conventional analog solutions. The TM9356 enables you to make and receive calls on either VHF, UHF or 7/800MHz radios from a single control head.

For analog operation, the TM9356 can also be configured as a crossband repeater.

Improve workforce safety with smart features such as Location Services, Tait GeoFencing, and Lone Worker functionality.

A range of control head options are available for TM9356 mobiles. ¹



Large Control Head (LCH): Built-in 3W Speaker



Hand Held Control Head



15W Rugged External Speaker



TCH4: High Resolution Color Display, Built-in 4W Speaker, Remote Mount



TCH6: High Resolution Color Display, Built-in Keypad, Remote Mount

Improve workforce safety

- Lone Worker as standard
- Tait GeoFencing Option for Automated Location Controlled Behavior
- Crystal-clear voice so the operator and user will understand the message
- Emergency calls have priority access to the network, and can be integrated with a GNSS location solution
- Blast Alarms and Audible Alerts in DMR modes

Tait GeoFencing Automation

- Radios can automatically take a range of actions based on location, such as change modes, send messages, hazardous area alert, activate lone worker features, or activate radio I/Os to turn lights on
- Independent of the network, dispatch, or any other software applications

Highly flexible and designed for demanding environments

- Rugged design exceeds MIL-STD-810G tests for humidity, salt fog, vibration, shock and solar radiation and is IP54 rated for protection against dust and splashing water
- Control head options include high definition color screen and Hand Held Control Head
- Remote mount options 19ft and 40ft (6m and 12m) options
- [Refer to Control Head Options brochure for more information](#)

High-performance voice communications capabilities

- VHF and UHF dual band capability
- Make and receive calls on either VHF or UHF radios from a single control head. Important calls won't be missed - with dual receive functionality, both radio bodies independently scan their channels at the same time - communications received by either radio body will be brought to the foreground
- Crossband repeater can be configured for analog operation - communications received on one frequency band can be instantly transmitted on the other frequency band
- Dual mode provides DMR Tier 2 conventional digital and conventional FM analog operation
- Open DMR standard provides choice and interoperability
- Large channel capacity with support of up to 4,000 channels per band
- Channel Authorization for DMR Tier 2 gives users confidence their call will be heard
- Proceed to Talk Tone available in all modes, for consistent operation
- Scanning modes include: priority, dual priority, zone, and background scan – groups are editable
- Individual calls provide privacy
- Optional DES or AES encryption for operation in digital mode.

Improve your organization's efficiency

- Text messaging for enhanced and unambiguous communications
- Pre-defined status messages for fast notification and response in common situations

Data Services

- Embedded data for location
- Short data messages for location, status and text
- Internal and external GNSS options available to improve efficiency and safety (please refer to Tait Mobiles catalog)
- CCDI connectivity to the mobile for short data and control messages in conventional mode

TM9300 Options and Accessories

- A range of audio accessories are available including microphones, speakers and installation options
- Options board space for Tait-developed or third-party options boards
- Digital and analog interfaces allow a range of accessory options for the TM9300
- Variety of vehicle installation kits for different mounting options
- [Refer to Tait Mobile Options and Accessories catalog for more information](#)

Color Options

- TM9300 mobile Hand Held Control heads are available in black, yellow, green and red, and Large Control Heads in black, yellow, and green.
- Different color options make it easier for workgroups to identify their equipment in the field

TM9356

SPECIFICATIONS

GENERAL

Frequency stability	±0.5ppm (-22°F to 140°F/-30°C to 60°C)
Networks	26
Channels/zones (per frequency band / radio body)	4,000 channels/100 zones
Scan groups (per frequency band / radio body)	300 with up to 50 members each
Dimensions (DxWxH)	
Control head (TCH4/TCH6)	2.8 x 7.0 x 2.0in (72 x 178 x 52mm)
Radio body - 25W	6.9 x 6.3 x 2.1in (175 x 160 x 52mm)
Radio body - 30/35/50W	7.7 x 6.3 x 2.1in (195 x 160 x 52mm)
Weight	
Control head (TCH4/TCH6)	0.62lb (0.28kg)
Radio body - 25W	2.6lb (1.2kg)
Radio body - 30/35/50W	3.1lb (1.4kg)
Channel spacing	6.25/12.5/15/20/25/30kHz
Frequency increment/channel step	2.5/3.125/5/6.25kHz
Operating temperature	-22°F to 140°F (-30°C to 60°C)
Water and dust protection	IP54
ESD rating	+/-4kV contact discharge and +/-8kV air discharge
Rated audio	3W internal speaker or external speaker
Power supply	DC: 10.8-16VDC
Digital Protocol	DMR: ETSI TS 102 361-1 V2.6.1, -2 V2.5.1, -3 V1.3.1, -4 V1.12.1
General System Design	ETSI TR 102 398 V1.5.1
Signaling options (Analog)	MDC1200 encode and decode, Two tone decode, PL (CTCSS), DPL (DCS), Selcall
Vocoder type	AMBE +2™

TRANSMITTER	VHF	UHF	700/800MHZ #
Frequency range	136-174MHz (B1) 174-225MHz (CO) ^P	378-470MHz (HK) ⁺ 400-470MHz (H5) 450-520MHz (H7)	757-870MHz (K5)
Output power			
25W Radio bodies	25W, 10W, 5W, 1W	25W, 10W, 5W, 1W	NA
High Power radio bodies	50W, 25W, 15W, 10W	40W, 20W, 15W, 10W	35/30W, 25W, 10W, 2W
Input current			
Standby Current	0.1A	0.1A	0.1A
25W Models	<5.5A	<6A	NA
High Power models	<10.5A	<10.5A	<10.5A
FM Hum and noise (Analog)			
12.5kHz	-40dB	-40dB	-40dB
25kHz ²	-45dB	-45dB	-45dB
Adjacent channel power - static (Analog)			
@ 12.5kHz offset	-60dB	-60dB	-60dB
@ 25kHz offset ²	-70dB	-70dB	-70dB
Adjacent channel power - static (DMR)			
ETS 300-113	12.5kHz: 60dB	12.5kHz: 60dB	12.5kHz: 60dB
Conducted/radiated emissions			
25W: -36dBm		25W: -36dBm	
50W: -20dBm		40W: -20dBm	30/35W: -20dBm
Audio response (Analog)	+1/-3dB	+1/-3dB	+1/-3dB
Audio distortion (Analog)	2.5% @1kHz, 60% deviation	2.5% @1kHz, 60% deviation	2.5% @1kHz, 60% deviation
Duty cycle	25W: 2min Tx, 4min Rx for 8 hrs @ 140°F (+60°C), 5W: continuous @ 104°F (+40°C) 30/35/40/50W: 1min Tx, 4min Rx for 8 hrs @ 140°F (+60°C)		

Supports 700 A-Block frequencies (757-758MHz Tx & Rx; 787-788MHz Tx)

^P 25W model only.

² 25W model only.

⁺ 40W model only.

TM9356

SPECIFICATIONS



RECEIVER	VHF	UHF	700/800MHZ #
Frequency range	136-174MHz (B1) 174-225MHz (C0)	378-470MHz (HK) 400-470MHz (H5) 450-520MHz (H7)	757-776MHz & 850-870MHz (K5)
Sensitivity (typical)			
Analog (12dB SINAD)	-120dBm (0.22µV)	-120dBm (0.22µV)	-120dBm (0.22µV)
DMR (1% BER (ETS300-113))	-119dBm (0.25µV)	-119dBm (0.25µV)	-119dBm (0.25µV)
DMR (5% BER)	-123dBm (0.16µV)	-123dBm (0.16µV)	-123dBm (0.16µV)
Intermodulation rejection			
EIA603E	76dB	70dB	75dB
ETS 300-113	70dB	70dB	70dB
Spurious response rejection			
EIA603E	80dB	75dB	70dB
ETS 300-113	70dB	70dB	70dB
FM hum and noise (Analog)	12.5kHz: -40dB 25kHz: -45dB	12.5kHz: -40dB 25kHz: -45dB	12.5kHz: -40dB 25kHz: -45dB
Conducted spurious emissions	-57dBm	-57dBm	-57dBm
Selectivity (Analog)			
EIA603E (2 Tone)	12.5kHz: 52dB 25kHz: 73dB	12.5kHz: 50dB 25kHz: 70dB	12.5kHz: 50dB 25kHz: 70dB
ETS 300-086	12.5kHz: 62dB 25kHz: 73dB	12.5kHz: 60dB 25kHz: 70dB	12.5kHz: 60dB 25kHz: 70dB
Optional external speaker output	15W	15W	15W
Audio distortion (rated audio)	2%	2%	2%

MILITARY STANDARDS 810C, D, E, F AND G

Applicable MIL-STD Method	Method	Procedure	Applicable MIL-STD Method	Method	Procedure
Low Pressure	500.5	2	Humidity	507.5	2
High temperature	501.5	1,2	Salt Fog	509.5	1
Low temperature	502.5	1,2	Sand & Dust	510.5	1, 2
Temperature shock	503.5	1	Vibration	514.5	1
Solar radiation	505.5	1	Shock	516.5	1,5,6
Rain	506.5	1,3			

REGULATORY DATA

	USA (FCC)	CANADA (ISED)	EUROPE /UK(CE) ³ E-MARK	AUSTRALIA/NEW ZEALAND (AS/NZ) ³
VHF (136-174MHz)	✓	✓	✓	✓
VHF (174-225MHz)	✓	-	✓	-
UHF (378-470MHz & 400-470MHz)	✓	✓	✓ ⁴	✓ ⁵
UHF (450-520MHz)	✓	✓	-	✓ ⁵
700/800MHz	✓	✓	-	-

Please note: Not all features are supported in all models or modes of operation - Contact your local Tait representative for more information.

Supports 700 A-Block frequencies (757-758MHz Tx & Rx; 787-788MHz Tx)

¹ Please refer to the Mobile Control Heads brochure for more information.

² Wideband operation is not available in the USA in some bands.

³ 25 Watt models only.

⁴ 400-470MHz band only.

⁵ The 25W UHF band radios are approved for use in Citizen Band in Australia and New Zealand when programmed to meet the requirements of AS/NZS4365.

Tait cannot guarantee full performance to the published specifications when the 378-470MHz and 400-470MHz band radios is operating at the CB frequencies.

TAIT DMR SOLUTION

Backed by our proven radio network expertise, the TM9356 mobile is part of our larger DMR offering. The Tait DMR solution consists of terminals, infrastructure, applications, services and integration with third party interfaces to ensure that your organization can reap all the benefits of the spectrally-efficient DMR standard in a mission critical environment.

Tait has taken every care in compiling this specification sheet, but we're always innovating and therefore changes to our models, designs, technical specification, visuals and other information included in this specification sheet could occur. For the most up-to-date information and for a copy of our terms and conditions please visit our website www.taitcommunications.com.

The words "Tait", "Tait Unified", the "Tait" logo and "Tait Unified" logo are trademarks of Tait International Limited.

Tait International Limited facilities are certified for ISO 9001:2015 (Quality Management System), ISO 14001:2015 (Environmental Management System) and ISO 45001:2018 (Occupational Health and Safety Management System) for aspects associated with the design, manufacture and distribution of radio communications and control equipment, systems and services. In addition, all our Regional Head Offices are certified to ISO 9001.

www.taitcommunications.com

© Tait International Limited 2024. Tait_SS_TM9356_v1.6

